System 636® Flame Spread & Smoke Development Ratings

TOLL FREE CANADA: (866) 473-9462

www.ipexinc.com

TOLL FREE U.S.: (800) 463-9572

www.ipexamerica.com

FLUE GAS VENTING SYSTEMS

IPEX is pleased to announce Flame Spread Rating and Smoke Developed Classification listings for our System 636 Flue Gas Venting pipe. System 636 Class IIA (PVC) and IIB (CPVC) pipe compounds were tested in accordance with ULC S102.2 and the resultant listings will give users an expanded range of permissible areas for installation.

System 636 PVC pipe, which is approved for use up to 65°C, exhibits a Flame Spread rating of 10.

System 636 PVC is now approved for use in:

 Noncombustible buildings, as detailed in clause 3.1.5.16 of the National Building Code (NBC)

System 636 CPVC pipe is now approved for use in:

- Noncombustible buildings, as detailed in clause 3.1.5.16 of the National Building Code (NBC)
- Air plenums, as per NBC article 3.6.4.3.(1)
- Buildings deemed to be high-rises, as per NBC article 3.2.6.
- System 636 CPVC pipe, which is approved for use up to 90°C, achieved a Flame Spread rating of 10 and Smoke Development classification of 25.

To access the Flame Spread ratings and Smoke Developed classifications for IPEX products

- Go to http://database.ul.com/cgibin/XYV/template/LISCANADA/1FRAME/index.html
- 2. Enter "IPEX" in the company name
- 3. Hit search
- 4. Click the "Link to File" for the "Plastic Materials" listing



Products manufactured by IPEX Inc. and distributed in the United States by IPEX USA LLC. System636® is a trademark of IPEX Branding Inc.



TEMESTIP081103R